



Printing date 15.03.2013

Revision: 15.03.2013

#### **1** Identification of the substance/mixture and of the company/undertaking

- · Product identifier
- · Trade name: REVITALCOLOR AG
- Article number: RAG ver. 55
- · Relevant identified uses of the substance or mixture and uses advised against
- Water-based coating REVITALCOLOR AG, RAG ver. 55.
- · Product category

REVITALCOLOR AG is an exterior microfibre reinforced waterborne anti-mildew acrylic paint.

· Application of the substance / the preparation

The coating REVITALCOLOR AG resists algae and mildew growth and contains special water-repellent additives(siloxanes). It is a durable coating which provides an excellent weather and ageing resistance, resistance to the low and increased temperature and good resistance in industrial and sea areas. REVITALCOLOR AG bridges hairline cracks (in combination with undercoat JUBOSIL EX). It is recommended for longlasting protection of old decorative plasters and renders. It could be used as a special equalizing coating for tinted mineral and silicate decorative renders.

• Details of the supplier of the safety data sheet

• Manufacturer/Supplier: JUB d.o.o. Dol pri Ljubljani 28 1262 DOL PRI LJUBLJANI SLOVENIA T: + 386 1 5884 183 F: + 386 1 5884 250 E: info@jub.si

Further information obtainable from: Product safety department: TRC JUB d.o.o.
Branko Petrovic, MSc
T: +386 1 5884 185
F: +386 1 5884 227
E: branko.petrovic@trc-jub.si
Emergency telephone number:

During normal opening times (8 - 16h CET) Group JUB: +386 1 5884 185

United Kindom: NPIS 0870 600 6266

#### **2** Hazards identification

· Classification of the substance or mixture

The product is classified as dangerous mixture harrmful to aquatic organisms in accordance with the regulations on classification of chemicals (Regulation on the classification, and in particularly EU Directives 1999/45/EC and 1967/548/ES, and in accordance with the CLP Regulation 2008/1272/ES), since it contains an algaecide active ingredient.

· Classification according to Regulation (EC) No 1272/2008

The product is not classified according to the CLP regulation.

· Classification according to Directive 67/548/EEC or Directive 1999/45/EC

*R52/53:* Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment. • Information concerning particular hazards for human and environment:

The product has to be labelled due to the calculation procedure of the "General Classification guideline for preparations of the EU" in the latest valid version.

(Contd. on page 2)

GB

Printing date 15.03.2013

Revision: 15.03.2013

#### Trade name: REVITALCOLOR AG

(Contd. of page 1) · Classification system: The classification is according to the latest editions of the EU-lists, and extended by company and literature data. · Label elements · Labelling according to EU guidelines: The product has been classified and marked in accordance with EU Directives / Ordinance on Hazardous Materials. · Hazard-determining components of labelling: terbutryn · Risk phrases: 52/53 Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment. · Safety phrases: 2 Keep out of the reach of children. 26 In case of contact with eyes, rinse immediately with plenty of water and seek medical advice. 28 After contact with skin, wash immediately with plenty of water. 29 Do not empty into drains. 46 If swallowed, seek medical advice immediately and show this container or label. 61 Avoid release to the environment. Refer to special instructions/safety data sheets. · Special labelling of certain preparations: Safety data sheet available for professional user on request. · Other hazards · Results of PBT and vPvB assessment · PBT: Not applicable. · vPvB: Not applicable.

# 3 Composition/information on ingredients

· Chemical characterization: Mixtures

Main components of the product REVITALCOLOR AG are emulsions which base on acrylic polymeric binders, microfibres, fine calcite and alluminosilicate fillers, titanium dioxide, cellulose thickeners and water. • **Description:** Mixture of substances listed below with nonhazardous additions.

· Dangerous components:

Very toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

CAS: 886-50-0	terbutryn	< 0.1%
EINECS: 212-950-5	₩ N R50/53	
	🚯 Aquatic Acute 1, H400; Aquatic Chronic 1, H410; 🚸 Acute Tox. 4, H302	

· Additional information:

The product is is water borne alkyd impregnation of wood containing with biocidal substances for wood preservation against molds, wood rot and insects.

For the wording of the listed risk phrases refer to section 16.

#### 4 First aid measures

· Description of first aid measures

- · After inhalation: Supply fresh air; consult doctor in case of complaints.
- · After skin contact: Immediately rinse with water.
- After eye contact: Rinse opened eye for several minutes under running water. Then consult a doctor.
- After swallowing: If symptoms persist consult doctor.
- Information for doctor:

• Most important symptoms and effects, both acute and delayed No further relevant information available.

(Contd. on page 3)

Printing date 15.03.2013

Revision: 15.03.2013

(Contd. of page 2)

Trade name: REVITALCOLOR AG

• *Indication of any immediate medical attention and special treatment needed No further relevant information available.* 

#### **5** Firefighting measures

- · Extinguishing media
- · Suitable extinguishing agents: Use fire extinguishing methods suitable to surrounding conditions.
- Special hazards arising from the substance or mixture No further relevant information available.
- · Advice for firefighters
- · Protective equipment: CO2, sand, extinguishing powder. Do not use water.

#### **6** Accidental release measures

· Personal precautions, protective equipment and emergency procedures Wear protective clothing.

• Environmental precautions:

Do not allow product to reach sewage system or any water course.

Inform respective authorities in case of seepage into water course or sewage system.

- Dilute with plenty of water.
- $\cdot$  Methods and material for containment and cleaning up:
- Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
- Reference to other sections
- See Section 7 for information on safe handling.
- See Section 8 for information on personal protection equipment.
- See Section 13 for disposal information.

### 7 Handling and storage

- · Handling:
- · Precautions for safe handling No special precautions are necessary if used correctly.
- · Information about fire and explosion protection: No special measures required.
- · Conditions for safe storage, including any incompatibilities
- · Storage:
- · Requirements to be met by storerooms and receptacles: Prevent any seepage into the ground.
- · Information about storage in one common storage facility:
- Do not store together with reducing agents, heavy-metal compounds, acids and alkalis. • Further information about storage conditions:
- Store under lock and key and with access restricted to technical experts or their assistants only.
- Storage class: Storage class: 12 Incombustible products
- Specific end use(s) No further relevant information available.

# 8 Exposure controls/personal protection

- Additional information about design of technical facilities: No further data; see item 7.
- · Control parameters
- · Ingredients with limit values that require monitoring at the workplace:
- The product does not contain any relevant quantities of materials with critical values that have to be monitored at the workplace.
- Additional information: The lists valid during the making were used as basis.
- · Exposure controls
- · Personal protective equipment:
- · General protective and hygienic measures: Wash hands before breaks and at the end of work.
- · Respiratory protection: Not required.

(Contd. on page 4)

-

GB

Printing date 15.03.2013

Revision: 15.03.2013

#### Trade name: REVITALCOLOR AG

· Protection of hands:

(Contd. of page 3)

GB

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye protection: Goggles recommended during refilling

#### 9 Physical and chemical properties · Information on basic physical and chemical properties · General Information · Appearance: Form: Fluid Colour: Different according to colouring · Odour: Mild · Odour threshold: Not determined. 10 · pH-value at 20 °C: · Change in condition Melting point/Melting range: Undetermined. **Boiling point/Boiling range:** 100 °C · Flash point: > 100 °C Not applicable. · Flammability (solid, gaseous): · Ignition temperature: Not determined. **Decomposition temperature:** Product is not selfigniting. · Self-igniting: Product does not present an explosion hazard. · Danger of explosion: · Explosion limits: Not determined. Lower: Not determined. Upper: · Vapour pressure: Not determined. · Density at 20 •C: 1.55 g/cm<sup>3</sup> · Relative density Not determined. · Vapour density Not determined. · Evaporation rate Not determined. · Solubility in / Miscibility with Fully miscible. water: · Partition coefficient (n-octanol/water): Not determined. · Viscosity: Dynamic: Not determined. Kinematic: Not determined. (Contd. on page 5)

Printing date 15.03.2013

Revision: 15.03.2013

#### Trade name: REVITALCOLOR AG

• Solvent content: Organic solvents: VOC (EC)	0.0 % 0.77 % The content of HOS: REVITALCOLOR AG max. 12 g/L VOC In accordance with the Directive 2004/42/EC the products is a coating of category A/c. EU VOC (cat. A/c) 40 g/l (2010)
Solids content:	70.0 %
• Other information	No further relevant information available.

#### 10 Stability and reactivity

· Reactivity

- · Chemical stability
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · Possibility of hazardous reactions No dangerous reactions known.
- $\cdot$  Conditions to avoid No further relevant information available.
- *Incompatible materials:* No further relevant information available.
- · Hazardous decomposition products: No dangerous decomposition products known.

# **11 Toxicological information**

- · Information on toxicological effects
- · Acute toxicity:
- · LD/LC50 values relevant for classification:
- oral. > 5000 mg/kg (Rat)
- *dermal.* > 5000 mg/kg(Rat)
- inhal. > 5000 mg/kg (Rat)
- · Primary irritant effect:
- on the skin: No irritant effect.
- on the eye: No irritating effect.
- · Sensitization: Sensitization possible through skin contact.
- · Additional toxicological information: Irritant

### **12** Ecological information

- · Toxicity
- Aquatic toxicity: No further relevant information available.
- · Persistence and degradability No further relevant information available.
- · Behaviour in environmental systems:
- · Bioaccumulative potential No further relevant information available.
- · Mobility in soil No further relevant information available.
- · Ecotoxical effects:
- **Remark:** Harmful to fish
- · Additional ecological information:
- General notes: Generally not hazardous for water Harmful to aquatic organisms
- Results of PBT and vPvB assessment
- · **PBT:** Not applicable.
- · vPvB: Not applicable.

(Contd. on page 6)

Printing date 15.03.2013

Revision: 15.03.2013

(Contd. of page 5)

Trade name: REVITALCOLOR AG

• Other adverse effects No further relevant information available.

#### **13 Disposal considerations**

· Waste treatment methods

· Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

• European	European waste catalogue		
08 01 11*	waste paint and varnish containing organic solvents or other dangerous substances		
	other construction and demolition wastes (including mixed wastes) containing dangerous substances		
15 01 02	plastic packaging		

· Uncleaned packaging:

• *Recommendation: Disposal must be made according to official regulations.* 

• Recommended cleansing agents: Water, if necessary together with cleansing agents.

4 Transport information	
· UN-Number · ADR, ADN, IMDG, IATA	The product REVITALCOLOR AG is not a substance or mixture classified in accordance with the provisions of ADR as dangerous for transport. Void
	1014
· UN proper shipping name · ADR, ADN, IMDG, IATA	Void
· Transport hazard class(es)	
·ADR	
· Class	- (-)
· ADN/R Class:	Void
· Packing group	
· ADR, IMDG, IATA	Void
· Environmental hazards:	
· Marine pollutant:	No
· Special precautions for user	Not applicable.
· Transport in bulk according to Annex	II of
MARPOL73/78 and the IBC Code	Not applicable.
· UN "Model Regulation":	-

# **15 Regulatory information**

 $\cdot$  Safety, health and environmental regulations/legislation specific for the substance or mixture

Following regulation was considered in the preparation of document: Legislation on the occupational health and safety, the chemical legislation and regulations on biocidal products, regulations on classification, packaging and labeling of chemical and biocidal products and requirements on safety data sheets for chemicals and biocidal products composition, as well as regulations on the management of packaging and packaging waste and waste.

In accordance with the current regulation the product is classified as a harmful mixture for aquatic organisms. General safety measures should be considered when working or handling with the product.

(Contd. on page 7)

GB -

Printing date 15.03.2013

Revision: 15.03.2013

#### Trade name: REVITALCOLOR AG

(Contd. of page 6)

· Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

# **16 Other information**

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

#### · Relevant phrases

- H302 Harmful if swallowed.
- *H400 Very toxic to aquatic life.*
- H410 Very toxic to aquatic life with long lasting effects.

R50/53 Very toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

#### · Recommended restriction of use

Claims contained in this document are based on our actual knowledge at the time of revision of this document. They do not undertake the properties of the product described in terms of the legal provisions for the pledge.

Placing this document as available does not unbind the product customer from its responsibility to comply with all relevant laws and regulations applicable for this product. This is especially valid in the case of product resale or resale of its mixtures or manufactured products from other areas of law and industrial property rights of third parties. If the product described above is changed by crafting or mixing with other materials, it is not possible to transfer claims from this document onto a newly made product, unless otherwise specified. In the case of product re-packaging the customer must attach the required relevant safety information as well.

· Department issuing MSDS: Product safety department

· Contact:

Branko Petrovic, MSc.

*T*: + *386 1 5884 185* 

E: branko.petrovic@trc-jub.si

· Abbreviations and acronyms:

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road) IMDG: International Maritime Code for Dangerous Goods

IMDG: International Maritime Code for Dangerous Goods IATA: International Air Transport Association

GHS: Globally Harmonized System of Classification and Labelling of Chemicals

- VOC: Volatile Organic Compounds (USA, EU)
- *LC50: Lethal concentration, 50 percent*
- LD50: Lethal dose, 50 percent

GB -