



Printing date 30.09.2015

Revision: 24.01.2014

SECTION 1: Identification of the substance/mixture and of the company/undertaking

· 1.1 Product identifier

· Trade name: HIDROZOL ELASTIK

- · Article number: HDE ver. 4
- · 1.2 Relevant identified uses of the substance or mixture and uses advised against

Cement flexible waterproofing compound HIDROZOL ELASTIK, HDE.

· Product category

HIDROZOL ELASTIK is industrially prepared compound used for the manufacture of a waterproofing compound for waterproof protection of vertical and horizontal surfaces of water reservoirs, elements of sewage systems and similar buildings, for waterproof protection of surfaces of bathrooms - where interior walls of lightweight buildings are usually made of gypsum-cardboards - balconies, terraces and pools prior to the application of ceramic coatings, as well as for protection of parts of buildings built into the ground – tunnels, culverts, supporting and pillar walls, concrete fences and similar - against the entry of soil damp and water.

· Application of the substance / the mixture

HIDROZOL ELASTIK complies with requirements for buildings intended for extraction, storage and preparation of drinking water.

HIDROZOL ELASTIK is flexible waterproofing compound, dry industrially prepared mortar based on cement. It is used for:

- Flexible waterproof protection in bathrooms, on balconies, terraces and in pools before ceramic linings are installed;

- The manufacture of flexible waterproof protection of external and internal concrete and cement surfaces;

- Protection of parts of construction buildings that are built into the ground against the entry of soil damp and water.

Declaration of conformity for use in contact with drinking water has been obtained; the product complies with requirements for buildings intended for extraction, storage and preparation of drinking water; it is flexible and provides long-lasting waterproof protection; excellent adhesion onto the surface (also on old ceramics); it prevents concrete degradation; protection against the positive and the negative water pressure; easy and simple application of a ceramic lining; the possibility of painting and other decorative linings; it effectively protects parts of buildings against the entry of soil damp; intended for demanding surfaces.

The product is a chemical compound characterised by low content of hazardous substances. It has been verified that, apart from cement, the product does not contain any other hazardous and volatile organic substances and heavy metals.

 \cdot 1.3 Details of the supplier of the safety data sheet

• Manufacturer/Supplier: JUB d.o.o. Dol pri Ljubljani 28 1262 DOL PRI LJUBLJANI SLOVENIA T: + 386 1 5884 183 F: + 386 1 5884 250 E: info@jub.si

Further information obtainable from: Product safety department: TRC JUB d.o.o.
Branko Petrovic, MSc
T: +386 1 5884 185
F: +386 1 5884 227
E: branko.petrovic@trc-jub.si
1.4 Emergency telephone number:

(Contd. on page 2)

GB

Printing date 30.09.2015

Revision: 24.01.2014

(Contd. of page 1)

Trade name: HIDROZOL ELASTIK

During normal opening times (8 - 16h CET) Group JUB: +386 1 5884 185

Emergency number: 112 United Kindom: NPIS 0870 600 6266

SECTION 2: Hazards identification

· 2.1 Classification of the substance or mixture In accordance with Regulations on the classification of chemicals (Rules on classification and mainly directives EU 1967/548/EEC and 1999/45/EC, neither bound by the Regulation CLP 2008/1272/EC), the product is classified as a hazardous compound since it contains cement. · Classification according to Regulation (EC) No 1272/2008 GHS05 corrosion Eye Dam. 1 H318 Causes serious eye damage. GHS07 Skin Irrit. 2 H315 Causes skin irritation. Skin Sens. 1 H317 May cause an allergic skin reaction. · Classification according to Directive 67/548/EEC or Directive 1999/45/EC Xi; Irritant R41: Risk of serious damage to eyes. Xi; Sensitising R43: May cause sensitisation by skin contact. · Information concerning particular hazards for human and environment: The product has to be labelled due to the calculation procedure of the "General Classification guideline for preparations of the EU" in the latest valid version. · Classification system: The classification is according to the latest editions of the EU-lists, and extended by company and literature data. · 2.2 Label elements · Labelling according to Regulation (EC) No 1272/2008 The product is classified and labelled according to the CLP regulation. · Hazard pictograms GHS05 GHS07 · Signal word Danger · Hazard-determining components of labelling: Cement, portland, chemicals · Hazard statements H315 Causes skin irritation. H318 Causes serious eye damage. H317 May cause an allergic skin reaction. · Precautionary statements P101 If medical advice is needed, have product container or label at hand. (Contd. on page 3)

- GE

Printing date 30.09.2015

Revision: 24.01.2014

Trade name: HIDROZOL ELASTIK

	(Contd. of page 2)
P102	Keep out of reach of children.
P103	Read label before use.
P261	Avoid breathing dust/fume/gas/mist/vapours/spray.
P280	Wear protective gloves/protective clothing/eye protection/face protection.
P305+P351+P3	38 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P310	Immediately call a POISON CENTER/doctor.
P321	Specific treatment (see on this label).
P501	Dispose of contents/container in accordance with local/regional/national/international regulations.
· Additional infor	mation:
Safety data shee	t available on request.
· 2.3 Other hazard	ds
· Results of PBT of	and vPvB assessment
· PBT: Not applic	able.
• vPvB: Not applie	cable.

SECTION 3: Composition/information on ingredients

· 3.2 Chemical characterisation: Mixtures

Main ingredients of HIDROZOL ELASTIK are: cement, polymeric binder, quartz fillers, cellulose thickener and hydrophobic supplements.

· Description: Mixture of substances listed below with nonhazardous additions.

· Dangerous components:

0 1		
CAS: 65997-15-1	Cement, portland, chemicals	10.0 - 19.0%
EINECS: 266-043-4	🗙 Xi R37/38-41; 🗙 Xi R43	
	📀 Eye Dam. 1, H318; 🚸 Skin Irrit. 2, H315; Skin Sens. 1, H317; STOT	
	SE 3, H335	

· Additional information:

For the wording of the listed risk phrases refer to section 16.

SECTION 4: First aid measures

· 4.1 Description of first aid measures

• After inhalation:

Supply fresh air and to be sure call for a doctor.

In case of unconsciousness place patient stably in side position for transportation.

- After skin contact: Immediately wash with water and soap and rinse thoroughly.
- After eye contact: Rinse opened eye for several minutes under running water. Then consult a doctor.

• After swallowing: If symptoms persist consult doctor.

• 4.2 Most important symptoms and effects, both acute and delayed No further relevant information available.

• 4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

SECTION 5: Firefighting measures

- · 5.1 Extinguishing media
- · Suitable extinguishing agents:

CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

• 5.2 Special hazards arising from the substance or mixture No further relevant information available.

· 5.3 Advice for firefighters

· Protective equipment: No special measures required.

(Contd. on page 4)

Printing date 30.09.2015

Revision: 24.01.2014

Trade name: HIDROZOL ELASTIK

(Contd. of page 3)

SECTION 6: Accidental release measures

- · 6.1 Personal precautions, protective equipment and emergency procedures Wear protective clothing.
- 6.2 Environmental precautions: Do not allow to enter sewers/ surface or ground water.
- 6.3 Methods and material for containment and cleaning up: Pick up mechanically.
- 6.4 Reference to other sections See Section 7 for information on safe handling.
- See Section 8 for information on personal protection equipment.
- See Section 13 for disposal information.

SECTION 7: Handling and storage

- 7.1 Precautions for safe handling No special precautions are necessary if used correctly.
- Information about fire and explosion protection: No special measures required.
- · 7.2 Conditions for safe storage, including any incompatibilities
- · Storage:
- Requirements to be met by storerooms and receptacles: Prevent any seepage into the ground.
- · Information about storage in one common storage facility:
- Do not store together with reducing agents, heavy-metal compounds, acids and alkalis. • Further information about storage conditions:
- Store under lock and key and with access restricted to technical experts or their assistants only.
- · Storage class: Storage class: 13 Incombustible solid products
- 7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

- Additional information about design of technical facilities: No further data; see item 7.
- · 8.1 Control parameters

· Ingredients with limit values that require monitoring at the workplace:

65997-15-1 Cement, portland, chemicals

WEL Long-term value: 10* 4** mg/m³

*inhalable dust **respirable dust

• Additional information: The lists valid during the making were used as basis.

- · 8.2 Exposure controls
- · Personal protective equipment:
- General protective and hygienic measures: Immediately remove all soiled and contaminated clothing Wash hands before breaks and at the end of work. Avoid contact with the eyes.
- · Respiratory protection: Not required.
- Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the (Contd. on page 5)

- GB

Printing date 30.09.2015

Revision: 24.01.2014


Trade name: HIDROZOL ELASTIK

application.

· Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

• Eye protection:



· Risk management measures

It is recommended to use high-quality work clothing and protective equipment. Use only outfits that meet the following standards:

- Protective gloves that meet the criteria of BS EN 388 (Category II).
- Protective goggles must comply with standard BS EN 166
- Protective mask respirator for small dust particles must conform to standard BS EN 149.

SECTION 9: Physical and chemical properties

General Information		
Appearance:		
Form:	Powder	
Colour:	Light grey	
Odour: Odour threshold:	Odourless Not determined.	
pH-value at 20 °C:	11	
Change in condition		
Melting point/Melting range:	Undetermined.	
Boiling point/Boiling range:	Undetermined.	
Flash point:	Not applicable.	
Flammability (solid, gaseous):	Not determined.	
Ignition temperature:		
Decomposition temperature:	Not determined.	
Self-igniting:	Product is not selfigniting.	
Danger of explosion:	Product does not present an explosion hazard.	
Explosion limits:		
Lower:	Not determined.	
Upper:	Not determined.	
Vapour pressure:	Not applicable.	
Density at 20 °C:	$0.92 \ g/cm^3$	
Relative density	Not determined.	
Vapour density	Not applicable.	
Evaporation rate	Not applicable.	
Solubility in / Miscibility with		
water:	Insoluble.	
Partition coefficient (n-octanol/wat	er): Not determined.	
Viscosity:		
Dynamic:	Not applicable.	

(Contd. of page 4)

Printing date 30.09.2015

Revision: 24.01.2014

Trade name: HIDROZOL ELASTIK

	(Contd. of page 5
Kinematic:	Not applicable.
· Solvent content:	
Organic solvents:	0.0 %
VOC(EC)	0.00 %
	VOC content: not specified
	(the product is not subject to the Directive 2004/42/EC)
Solids content:	100.0 %
• 9.2 Other information	No further relevant information available.

SECTION 10: Stability and reactivity

· 10.1 Reactivity No further relevant information available.

- · 10.2 Chemical stability
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- 10.3 Possibility of hazardous reactions No dangerous reactions known.
- 10.4 Conditions to avoid No further relevant information available.
- \cdot 10.5 Incompatible materials: No further relevant information available.
- · 10.6 Hazardous decomposition products: No dangerous decomposition products known.

SECTION 11: Toxicological information

- · 11.1 Information on toxicological effects
- · Acute toxicity
- · LD/LC50 values relevant for classification:
- oral. > 2000 mg/kg (rat)
- *dermal.* > 2000 mg/kg(rat)
- inhal. > 2 mg/kg, 4h (rat)
- · Primary irritant effect:
- *Skin corrosion/irritation Causes skin irritation.*
- Serious eye damage/irritation Causes serious eye damage.
- Respiratory or skin sensitisation
- May cause an allergic skin reaction.
- · CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)
- \cdot Germ cell mutagenicity Based on available data, the classification criteria are not met.
- \cdot Carcinogenicity Based on available data, the classification criteria are not met.
- $\cdot \textit{Reproductive toxicity Based on available data, the classification criteria are not met.}$
- STOT-single exposure Based on available data, the classification criteria are not met.
- $\cdot \textbf{STOT-repeated exposure} Based on available data, the classification criteria are not met.$
- · Aspiration hazard Based on available data, the classification criteria are not met.

SECTION 12: Ecological information

- · 12.1 Toxicity
- Aquatic toxicity: No further relevant information available.
- 12.2 Persistence and degradability No further relevant information available.
- · 12.3 Bioaccumulative potential No further relevant information available.
- · 12.4 Mobility in soil No further relevant information available.
- · Additional ecological information:

· General notes:

Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

(Contd. on page 7)

GB

Printing date 30.09.2015

Revision: 24.01.2014

Trade name: HIDROZOL ELASTIK

- · 12.5 Results of PBT and vPvB assessment
- **PBT:** Not applicable.
- **vPvB:** Not applicable.

· 12.6 Other adverse effects No further relevant information available.

SECTION 13: Disposal considerations

· 13.1 Waste treatment methods

· Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

· European waste catalogue

17 09 04 mixed construction and demolition wastes other than those mentioned in 17 09 01, 17 09 02 and 17 09 03

15 01 01 paper and cardboard packaging

• Uncleaned packaging:

• Recommendation: Disposal must be made according to official regulations.

SECTION 14: Transport information

· 14.1 UN-Number · ADR, ADN, IMDG, IATA	HIDROZOL ELASTIK is not classified as a substance or compound which would be dangerous for transport in accordance with provisions of ADR. Void
, , , ,	Voiu
· 14.2 UN proper shipping name · ADR, ADN, IMDG, IATA	Void
· 14.3 Transport hazard class(es)	
· ADR, ADN, IMDG, IATA · Class	Void
· 14.4 Packing group · ADR, IMDG, IATA	Void
· 14.5 Environmental hazards: · Marine pollutant:	No
· 14.6 Special precautions for user	Not applicable.
· 14.7 Transport in bulk according to Annex I Marpol and the IBC Code	I of Not applicable.
· Transport/Additional information:	
· ADR · Limited quantities (LQ)	-
· UN "Model Regulation":	Void

SECTION 15: Regulatory information

• 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture In the preparation of the document, the following regulations have been taken account of: legislation on health protection at work, chemical legislation and regulation on biocidal products, rules on classification, packaging and labelling chemical and biocidal products and on safety data sheets for chemicals and biocidal products, as well as regulations on the management of packaging, packaging waste and waste.

(Contd. on page 8)

GB

(Contd. of page 6)

Printing date 30.09.2015

Revision: 24.01.2014

(Contd. of page 7)

Trade name: HIDROZOL ELASTIK

In accordance with the current chemical legislation, the product is classified as a hazardous substance or compound because it contains cement.

When working with and handling the product, only general precautionary measures need to be followed.

· Labelling according to Regulation (EC) No 1272/2008 -

· Chemical safety assessment -

• 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Relevant phrases

- H315 Causes skin irritation.
- H317 May cause an allergic skin reaction.

H318 Causes serious eye damage.

H335 May cause respiratory irritation.

R37/38 Irritating to respiratory system and skin.

R41 Risk of serious damage to eyes.

R43 May cause sensitisation by skin contact.

· Recommended restriction of use

Claims contained in this document are based on our actual knowledge at the time of revision of this document. They do not undertake the properties of the product described in terms of the legal provisions for the pledge.

Placing this document as available does not unbind the product customer from its responsibility to comply with all relevant laws and regulations applicable for this product. This is especially valid in the case of product resale or resale of its mixtures or manufactured products from other areas of law and industrial property rights of third parties. If the product described above is changed by crafting or mixing with other materials, it is not possible to transfer claims from this document onto a newly made product, unless otherwise specified. In the case of product re-packaging the customer must attach the required relevant safety information as well.

· Department issuing MSDS: Product safety department

· Contact:

mag. Branko Petrovič TRC-JUB d.o.o branko.petrovic@trc-jub.si

· Abbreviations and acronyms:

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road) IMDG: International Maritime Code for Dangerous Goods IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

VOC: Volatile Organic Compounds (USA, EU)

LC50: Lethal concentration, 50 percent LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

Skin Irrit. 2: Skin corrosion/irritation, Hazard Category 2

Eye Dam. 1: Serious eye damage/eye irritation, Hazard Category 1

Skin Sens. 1: Sensitisation - Skin, Hazard Category 1 STOT SE 3: Specific target organ toxicity - Single exposure, Hazard Category 3

* * Data compared to the previous version altered.

Version 1.0, 2.07.2013.

Version 2.0, 23.04.2014; Amending Chapter: 2., 3., 16.

GB